

Finger Safe Power Distribution Blocks

UL Approved for 100kA

- Mersen Finger-Safe PDB's meet k10A Short Circuit Current Rating (SCCR) per UL 1059
(Reference: UL File E73571)
- Preferred by electrical panel shops to meet latest requirements of NEC and UL508a
 - SCCR Rated
 - Touch Safe
 - Wide Product Offering
 - Availability



Mersen Part No.	Amps	SCCR	WIRE RANGE		REQUIRED OVERCURRENT PROTECTION					
			Line	Load	Class J (AJT, A4J, HSJ)	Class T (A3T/A6T)	RK1 (A2D/A6D) (A2K/A6K) HSRK	RK5 (TR/TRS)	Class G (AG)	Class CC (ATDR, ATQR, ATMR)
FSPDB1A	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB1C	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB2A	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB2C	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB3A	310	100KA	350-#6 & 2/0-#14	2/0-#14	400A	400A	400A	200A	60A	30A
FSPDB3C	310	100KA	350-#6 & 2/0-#14	2/0-#14	400A	400A	400A	200A	60A	30A