

gl-gG, aM Cylindrical Fuse-Links

Domestic and industrial cylindrical fuse-links

Mersen gl-gG and aM fuse-links cover a wide range of physical sizes and ampere ratings for 400, 500, and 690 volts AC. gl-gG and aM fuse-links are for industrial applications. Most ratings are available with an optional indicator. All industrial fuse-links have the option of a built-in striker. All cylindrical fuse-links have ceramic bodies and silver-plated ferrules.

gl-gG

Full Range Protection

- 4 physical sizes from 8 x 31mm to 22 x 58 mm
- 400, 500 and 690 Volt ratings - 0.5A through 125A
- Most ratings available with indicator
- Meet IEC, NFC and UNE standards
- Approved by Lloyds Register of Shipping and Bureau Veritas

aM

Short Circuit Protection

- 4 physical sizes from 8 x 31mm to 22 x 58mm
- 400, 500 and 690 Volt ratings - 16A through 125A
- Most ratings available with indicator
- Meet IEC, NFC and UNE standards
- Approved by Lloyds Register of Shipping and Bureau Veritas

gl-gG

Full Range Protection Fuse-links with Striker

- 2 sizes-14 x 51mm and 22 x 58mm
- 400, 500 and 690 Volt ratings - 4A through 125A
- All ratings include striker
- Meet IEC, NFC and UNE standards
- Approved by Lloyds Register of Shipping and Bureau Veritas

aM

Short Circuit Protection Fuse-links with Striker


- 2 sizes - 14 x 51mm and 22 x 58mm
- 400, 500 and 690 Volt ratings - 2A through 125A
- All ratings include striker
- Meet IEC, NFC and UNE standards
- Approved by Lloyds Register of Shipping and Bureau Veritas




aM Cylindrical Fuse-Links

Catalog Numbers, Ratings – aM (Optional Blown-Fuse Indicator)

Size (mm x mm)	Rated In Current (A)	Rated Voltage	Catalog Number		Interrupting Rating (A)	Standard Pack/Ctn
			w/o Indicator	w Indicator		
8x31	1	400V	15511-G		20,000	10/100
	2		15513-G			
	4		15519-G			
	6		15523-G			
	8		15527-G			
	10		15531-G			
10x38	0.16	500V	16503-G		120,000	10/100
	0.25		16507-G			
	0.5		16509-G			
	1		16511-G	16711-G		
	2		16513-G	16713-G		
	4		16519-G	16719-G		
	6		16523-G	16723-G		
	8		16527-G	16727-G		
	10		16531-G	16731-G		
	12		16533-G	16733-G		
	16		16535-G	16735-G		
	20		16537-G	16737-G		
	25		16539-G	16739-G		
	32		16543-G			
14x51	0.25	690V	17507-G		80,000	10/50
	0.5		17509-G			
	1		17511-G			
	2		17513-G			
	4		17519-G			
	6		17523-G			
	8		17527-G			
	10		17531-G			
	12		17533-G			
	16		17535-G			
	20		17537-G			
	25		17539-G			
	32		17543-G			
	40		17547-G	120,000		
	45		17549-G			
	50		17551-G	400V		
22x58	4	690V	18519-G		80,000	10/50
	6		18523-G			
	8		18527-G			
	10		18531-G			
	12		18533-G			
	16		18535-G			
	20		18537-G			
	25		18539-G			
	32		18543-G			
	40		18547-G			
	50		18551-G			
	63		18055-G			
	80		18559-G			
	100		18563-G	500V		
125	18565-G	400V				



15519-G



16535-G




17535-G



18555-G

Dimensions (mm)


Fuse Size	A	B	C
8 x 31	8.5	31.5	6.3
10 x 38	10.3	38	10.5
14 x 51	14.3	51	13.8
22 x 58	22.2	58	16.2



aM Cylindrical Fuse-Links

Catalog Numbers, Ratings – aM with Striker

Size (mm x mm)	Rated In Current (A)	Rated Voltage	Catalog Number	Interrupting Rating (A)	Standard Pack/Ctn			
14 X 51	1	500V	17911-G	120,000	10/50			
	2		17913-G					
	4		17919-G					
	6		17923-G					
	8		17927-G					
	10		17931-G					
	12		17933-G					
	16		17935-G					
	20		17937-G					
	25		17939-G					
	32		17943-G					
	40		17947-G					
	45		17949-G					
	50	400V	17951-G					
22 X 58	4	690V	18919-G	80,000	10/50			
	6		18923-G					
	8		18927-G					
	10		18931-G					
	12		18933-G					
	16		18935-G					
	20		18937-G					
	25		18939-G					
	32		18943-G					
	40		18947-G					
	50		18951-G					
	63		18955-G					
	80		500V			18959-G	120,000	
	100		400V			18963-G		
	125					18965-G		



17947-G



18951-G

Striker



BEFORE



AFTER

Dimensions (mm)

Fuse Size	A	B	C	D	E
14 x 51	14.3	51	13.8	7.5	3.8
22 x 58	22.2	58	16.2	7.5	3.8

