



REV	DATE	ECO	DESCRIPTION	BY	CK
00	3/94		RELEASED	30	

P/N	WIRE RANGE & TORQUE (IN-LBS)				U/L		CSA
	PRIMARY		SECONDARY		FILE #	GUIDE #	REPORT #
	RANGE	TORQUE	RANGE	TORQUE			
66203	3/8" STUD	228	3/8" STUD	228	E73571	XCFR2	LR69363

CONTROLLED COPY
 ISSUED TO *Newburyport*
 DATE *MAR 24 1994*

2. (1)3/8-16 X 1 1/2 X (1)3/8-16 X 1 1/2 3 POLE, 600V.
1. MATL COMPOSITION AND RATING:
 BASE-THERMOPLASTIC-125°C RTI
 CONNECTOR-COPPER ALLOY-TIN PLATED.

NOTES: UNLESS OTHERWISE SPECIFIED

P/N 66203 (CU ONLY)

	<small>GOULD INC. P.O. BOX 729 HAVELock FALLS, TX 78054</small>		<small>TOLERANCE TO BE APPLIED UNLESS OTHERWISE SPECIFIED: .0004-.0005, .0004-.0005, .004-.011, .04-.02, 2/24/32 UNSPECIFIED ANGLES 45°, SPECIFIED ANGLES 90° DIMENSIONS APPLY AFTER PLATING ALL SURFACES TO BE 125° UNLESS OTHERWISE SPECIFIED</small>	
	<small>CIRCUIT PROTECTION DIV.</small>	<small>DATE:</small> 3/94	<small>INT. REL.</small>	<small>SCALE:</small> NONE
<small>DRAWN BY:</small> KDS	<small>CHECKED BY:</small> GHO	<small>DATE:</small> 3/94	<small>REFDOC:</small>	
<small>DESCRIPTION</small> PDB, 3/8 X 3/8 3 POLE			<small>IDENTIFICATION NO. & REVISION</small> 05B0474 00	