

# IN-LINE FUSE HOLDERS



**SFRT**

Twist-Lock In-Line Fuseholders for FSFE fuses. Used at 32V or less with fuses rated up to 20A when proper spring for fuse size is installed.

Includes fuse listed

### Standard Fuse Ampere Ratings

CATALOG NUMBER	FUSE INSTALLED
SFRT4	FSFE4
SFRT6	FSFE6
SFRT7-1/2	FSFE7-1/2
SFRT9	FSFE9
SFRT14	FSFE14
SFRT20	FSFE20




**SFRB**

Bayonet Knob In-Line Fuseholders for FSFE fuses. Used at 32V or less with fuses rated up to 20A when proper spring for fuse size is installed.

### Standard Fuse Ampere Ratings


CATALOG NUMBER	FUSE INSTALLED
SFRB4	FSFE4
SFRB6	FSFE6
SFRB7-1/2	FSFE7-1/2
SFRB9	FSFE9
SFRB14	FSFE14
SFRB20	FSFE20

**C**



**SFRG**

In-Line Fuseholder for 5 x 20mm fuses. Max. current rating for 5x20mm fuses - 10A @ 32V



**FSFE**

Glass Body  
Fast Acting

4A through 30A, 32VAC/DC - UL Listed



### Catalog Number: SFRU

Universal In-Line Fuseholder - supplied with 15" loop of #14 AWG red vinyl insulated wire frame and three springs in different lengths to accommodate FSFE size fuses.

CATALOG NUMBER	AMPERE RATING	VOLTS	FUSE LENGTH
FSFE4	4A	32V	5/8"
FSFE6	6A	32V	3/4"
FSFE7-1/2	7-1/2A	32V	7/8"
FSFE9	9A	32V	7/8"
FSFE14	14A	32V	1-1/16"
FSFE20	20A	32V	1-1/4"
FSFE30	30A	32V	1-7/16"

### Standard Fuse Ampere Ratings